



POLY *Western Washer*

Poly water tank c/w baffle, 18" manhole & locking cover, mounted on highway tow single axle chassis c/w washer pump mounting plate, 14" wheels & tyres

- High performance range with petrol or diesel engine choices to fulfil your needs.
- Saves you, and your work force, time as removes need to locate a water supply out on location - fill your bowser at base and take your water with you.
- Many uses including cleaning of plant machinery on site, road signs, street cleaning, graffiti removal, etc.
- Standard spec includes hose, adjustable trigger lance and a holder for safe storage of lance during transportation.
- Simply select the engine required from the chart on page 96 of our catalogue.

Specification

Standard tank fitting specification: 18" manhole with screw lid & centre 5" vented fill cap : 2" fast drain port : 3/4" lockable rear draw off tank : lockable manhole cover. Tank filter, 3/4" outlet valve, and 1/2" return.

Capacity (brim full) Litres: 500	Suspension: Single rubber suspension axle (1000kg gross)
Capacity (brim full) Gallons: 110	Brake specification: 200 x 50 auto reverse brakes
Dimension Length (mm): 3100	Chassis: 5mm hot dipped galvanised chassis frame
Dimension Width (mm): 1340	Wheels & Tyres: 2 off 185R14 8ply
Dimension Height (mm): 1100	Mudguards: Moulded polythene
Tank Material (thickness): 6mm - 8mm polythene	Jockey Wheel: 48mm telescopic adjustable
Weight* Empty Kg: 265	Lighting: To full EU standards wired to 7pin plug
Weight* Full Kg: 900**	Coupling specification: Knott KRV20. Ball or eye coupling as required
Rear Support Leg: 1 x fitted	Design approvals: Trailer equipment conforms to EC directives

Notes

* Weight includes chassis & tank

** Max axle laden weight